

TECHNICAL DATA SHEET

DPXM250

White opaque high grade polyester based synthetic print media with a matt finish.

Water and tear resistant, DPIM085 is extremely suitable for quick 'print and turn' jobs.

The growing range of applications includes indoor and outdoor POS signage, menu cards, tab sheets, labels and tags, just to name a few.

Property	Test method	Unit	DPXM250
Thickness Average	ASTM D-6988	μm	250 ± 15
Weight		g/m ²	300
Shrinkage	Internal test at 95°C/203°F	%	0,2
Brittleness	Internal test	°C (°F)	-40 (-40)
Initial tear strength	ASTM D1004	N	100
Stiffness	ISO 2493	mN	48
Conductivity	DIN IEC 93	Ω/□	>1 X 10 ⁹
BEKK smoothness	ISO 5627	Sec	125-175
Opacity	ISO 2471	%	94
Brightness	ISO 2470C		95
Whiteness Cie	ISO 11475		98
Gloss 85°	ISO 2813		3-10
Mass Density	ISO 534	g/cm ³	1.25 ± 0.05
Shelf Life	At least 24 months		
Fire Class	Information upon request		

Alon Tavor Ind. Zone, Israel

www.jolybar.com

jolybar@jolybar.com

+972-4-6407333