

13oz/ 440gsm Super Smooth Blockout 440
PRODUCT: BLOW-440
FEATURES / APPLICATIONS:

- Good opacity
- Printable on both sides with uniform printing quality
- Best suited for indoor applications or outdoors under low stress conditions when banner opacity is required
- Matte & gloss surfaces available

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	440g/m ²	13oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	275x275 dtex	250x250 denier
Tensile Strength	DIN EN ISO 1421	665x270 N/5cm	78x31 lbs/inch
Tear Strength	DIN 53363	100x50 N	22x 11lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 320 cm	126 inch

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Screen Printing	Dye Transfer	Dye Direct	
<input type="checkbox"/>			

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Soyang Hangzhou Factory

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982