

## 11oz/ 380gsm Standard Mesh With Liner

**PRODUCT:** MESH-1812V

**STRUCTURE:** BASE FABRIC COATED WITH PVC

**FEATURES / APPLICATIONS:**

- 40% air-flow through
- Coming with a PVC backing which makes the printing and feeding much easier
- Printable on two sides with UV ink
- Widely used for scaffolding, theatrical, TV backdrops, hanging display& large format advertisement

**MATERIAL DETAILS**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	380g/m <sup>2</sup>	11oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn	DIN EN ISO 2060	550 x 1100 dtex	500 x 1000 denier
Tensile Strength	DIN EN ISO 1421	900x1100 N/5cm	101x128 lbs/inch
Tear Strength	DIN 53363	190x210N	42x 47lbs
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 320cm	126 Inch

**INK PRINTABILITY**

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

**Soyang Headquarter**

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

[www.soyang.net](http://www.soyang.net)

P. 0086-571-28918690  
F. 0086-571-28918695

**Soyang Europe Ltd**

38 Peel Industrial Estate, Bury, Manchester BL9 0LU UK.

[www.soyang.co.uk](http://www.soyang.co.uk)

P. 0044-870 112 7445  
F. 0044-870 112 7446

**Soyang Ibero-Africa**

Po Box 156, 2350-999 Torres Novas, Portugal

[www.soyang.pt](http://www.soyang.pt)

P. 00351-249-817813/4  
F. 00351-249-817815