

Popular Flag

PRODUCT: ST-110

STRUCTURE: BASE FABRIC COATED WITH PVC

FEATURES / APPLICATIONS:

- Transparent
- Good print through
- No fraying
- Perfect for flags & banners

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
STD Width	/	1.37m	54"
STD Length	/	50m	54.7yd
Flag Weight	/	110g/sq.m	3oz/sq.yd
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	77dtex	70denier
Tensile Strength	DIN EN ISO 1421	178 x108N/5cm	20x12 lbs/Inch
Tear Strength	DIN 53363	16x17N	3.6x4lbs

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	Water based
	<input type="checkbox"/>	<input type="checkbox"/>	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Headquarter

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690
F. 0086-571-28918695

Soyang Europe Ltd

38 Peel Industrial Estate, Bury, Manchester BL9 0LU UK.

www.soyang.co.uk

P. 0044-870 112 7445
F. 0044-870 112 7446

Soyang Ibero-Africa

Po Box 156, 2350-999 Torres Novas, Portugal

www.soyang.pt

P. 00351-249-817813/4
F. 00351-249-817815