

Soft-PVC 80µ, transparent glossy **K1132 T** Kraft paper, permanent

Technical Product Information

Grade characteristics

<b>Description</b>	Soft-PVC transparent glossy
<b>Application</b>	Decorative labels for cosmetics, food.
<b>Coating</b>	With certified Indigo-topcoat
<b>Approvals</b>	Complies with EU-Regulations: Packaging 94/62/EC ; Heavy Metal, PBB and PBDE
<b>F i m</b>	2003/11;
<b>Remarks</b>	Suitable for HP Indigo I

Description

Physical properties	Value	Unit	Test method
Caliper	80 ±5	µm	ISO 534
Stretch at break md	> 160	%	DIN 53455
Tear resistance md	> 26	Mpa	ISO 1924/1

**A**  
**d** Permanent adhesive P3:  
**h** High transparency, permanent copolymeric acrylate adhesive with controlled initial tack. Complies with the EN 71/3  
**e** (application on toys) and the European packaging directive 94/62/EC (heavy metals).

**s**

Physical properties	Value	Unit	Test method
Adhesion P3 → permanent	14 ± 6	N/25mm	FTM 1 24h on glass

**i**

Description

Liner H12:  
135g/m<sup>2</sup>, chlorine free bleached Kraftliner

**L**  
**i**  
**n**  
**e**  
**r**

Physical properties	Value	Unit	Test method
Substance	135	g/m <sup>2</sup>	ISO 536
Caliper	136	µm	ISO 534

Storage and application data

Recommended processing temperature

Product application temperature

Life expectancy

Shelf life at 23°C / 50% r.h.

min. + 5°C - 30°

up to + 90°C

1 year

1 year in original packing \*