

# TECHNICAL DATA SHEET

## DPIC250

### Product description:

- Clear PET 250  $\mu\text{m}$  with removable back paper
- Applications: Booklet binding, advertising products, signage, decoration
- Optimized for HP-Indigo printing machines
- Excellent ink adhesion
- Excellent machine runnability

Parameter	Value
Dimension (mm)	480X330 750X530
Thickness ( $\mu\text{m}$ )	250 $\pm$ 3
Heat Shrinkage (dry air at 150°C) (%)	MD $\leq$ 0.5, TD $\leq$ 1.5
Tensile Strength (kgf/mm <sup>2</sup> )	MD $\leq$ 18.0, TD $\leq$ 21.0
Surface	Gloss

### Processing Recommendations:

- Substrates should be climatized at room temperature 24 h before printing.
- Print at room temperature with relative humidity between 50-60%.

### Storage Conditions:

- Storage should be at temperatures of 10-30°C and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333

7.19