

# TECHNICAL DATA SHEET

## DDIG050

### Product description:

- White PET Gloss Self Adhesive 50my
- Applications: Label for advertising products, signage, decoration
- Outdoor and indoor use\*
- Adhesive high bond strength to polar and non-polar surfaces
- Optimized for HP-Indigo printing machines
- Excellent ink adhesion
- Excellent machine runnability

| Parameter                              | Value  |
|--|--|
| Dimension (mm)                         | 480 X 330<br>750 X 530   |
| Face Stock Thickness ( $\mu\text{m}$ ) | 50 $\pm$ 6   |
| Adhesive                               | Initial tack 10N/25mm (FTM9 glass)<br>Peel at 180 <sup>o</sup> 11N/25mm (FTM1) |
| Liner Thickness ( $\mu\text{m}$ )      | 200 $\pm$ 16   |
| Surface                                | White, Gloss   |

### Processing Recommendations:

- Substrates should be acclimatized at room temperature 24 h before printing.
- Print at room temperature with relative humidity between 50-60%.

### Storage Conditions:

- Storage should be at temperatures of 10-30°C and relative humidity of 50-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

\*Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

[www.jolybar.com](http://www.jolybar.com)

[jolybar@jolybar.com](mailto:jolybar@jolybar.com)

+972-4-6407333

1.20