

J87270 | SCM Matt 170

SPECIAL-COATED MATT PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	165	± 7
Thickness DIN EN ISO 534	µm	200	± 8
	mil	7.9	± 0.3
Colour Elrepho UVO (D65) ISO 2469	L	95,8	± 1,0
	a	-0,2	± 0,5
	b	-1,2	± 1,0
	delta b	12,3	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 150	
Opacity min. ISO 2469	%	> 95	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

◆ Inkjet water-based

◆ Inkjet latex

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

Certificates



DIN EN ISO 9706

KEY APPLICATIONS

Photo Retail

- Presentations
- Proposals
- Newsletters

Wall Decoration

- Posters
- Large-format photo prints

Sign & Display Graphics

- POS signage
- Exhibition graphics
- Commercial posters

BENEFITS & PROPERTIES

- Very smooth surface
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- Meets criteria for permanence according ISO 9706

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 01/2016