

TECHNICAL DATA SHEET

DDIG080

Product description:

- White Gloss PVC Self Adhesive 80my
- Applications: Label for advertising products, signage, decoration
- Optimized for HP-Indigo printing machines
- Excellent ink adhesion
- Excellent machine runnability

Parameter		Value
Dimension (mm)		460 X 320
		480 X 330
		750 X 530
Face stock	Thickness (µm)	80±8
	Stretch at Break md (%)	>150
	Tear Resistance md (mPa)	>25
Adhesive	Permanent Clear High-Tack Adhesive	
	Initial Peel Strength (N/25mm), FTM 1	17±3
	Final Peel Strength (N/25mm), FTM 1	20±3
Face stock + adhesive	Opacity (%)	>90%
Liner	Thickness (µm)	160±6
Surface		White Gloss

Processing Recommendations:

- Substrates should be acclimatized at room temperature 24 h before printing.
- Print at room temperature with relative humidity between 50-60%.

Storage Conditions:

- Storage should be at temperatures of 15-35°C and relative humidity of 30-60%. Do not expose to direct Sun light.
- Keeping the recommended storage conditions in original packaging will increase product shelf life up to 1 year.

Users should perform their own tests in order to verify the suitability for a specific application

Alon Tavor Ind. Zone, Israel

www.jolybar.com

jolybar@jolybar.com

+972-4-6407333

1.20