

8oz/270gsm Premium Mesh

PRODUCT: MESH-12

STRUCTURE: BASE FABRIC COATED WITH PVC

FEATURES / APPLICATIONS:

- 37% air-flow through
- Soft and clean surface
- Printable on two sides with UV ink
- Widely used for scaffolding, theatrical, TV backdrops, hanging display& large format advertisement
- A PVC backing is also available which prevents ink spray through when printing and makes the feeding easier

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	270g/m ²	8oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Tensile Strength	DIN EN ISO 1421	1520x1250 N/5cm	170x140 lbs/inch
Tear Strength	DIN 53363	280x223N	63x50lbs
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Width	N/A	Max 500cm	197 Inch

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Headquarter

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690
F. 0086-571-28918695

Soyang Europe Ltd

38 Peel Industrial Estate, Bury, Manchester BL9 0LU UK.

www.soyang.co.uk

P. 0044-870 112 7445
F. 0044-870 112 7446

Soyang Ibero-Africa

Po Box 156, 2350-999 Torres Novas, Portugal

www.soyang.pt

P. 00351-249-817813/4
F. 00351-249-817815